



REXINO
STAINLESS & ALLOYS

Inconel Flanges



Inconel Flanges, We are occupied in providing a superior range of **Inconel Flanges** to our customers, which is fabricated using premium quality raw fabrics and innovative engineering. We fabricate and provide several types of Inconel Flanges that are offered in ANSI, DIN, JIS, BS and ASME standards. We provide a full range of Inconel flanges with accurately drill holes for easy installation and unique features. Fabricated from quality raw material, supreme grade stainless steel, these Inconel Flanges are known for its unique characteristics, solid sturdy design and manufacture.

Profit **Inconel weld neck flanges** with an overwhelming welding neck, which is structured from a roundabout segment of steel plate holding a short co-pivotal opening in the center. Quality raw material guarantees durability and elite of these flanges. Accessible in distinctive shapes and sizes, these flanges are accessible at the most competitive prices.

Inconel Socket weld flanges are welded along the end connected with pipe so the pipework may be bolted to a different pipe with a related flange. Most of these flanges encourage easy interconnection as well as removal of the pipe. Manufactured from exceptional level connected with Inconel, our own choice of light weight flanges is available in different specifications at the most reasonable rates.

Currently **Inconel slip-on flange** with a solid, circular plate flange that is certainly ended up in the end of the pipe for welding. These cases of excellent slip on flanges adhere to intercontinental excellent specifications.

You can expect **Inconel blind flanges** which might be typically used for closing the end of pipe. Made of greatest high quality connected with Inconel, each of our range of blind flanges is durable, corrosion, ease installation and also rust repellent. These cases of blind flanges enables to close up the actual concludes connected with pipe, valves, force vessel openings as well as other programs, wherever one end must be blanked off.

Address	:	Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004
E-mail	:	info@rexinostainless.com , export@rexinostainless.com
Visit Us	:	www.rexinostainless.com
Contact Person	:	Mr. Bhavesh Chandan
Mobile	:	+91- 9920773453



Range : ½” NB to 12” NB

Standard : 150 LBS, 300 LBS, 600 LBS, 900 LBS, 1500 LBS, 2500 LBS , ASA 150#, ASA 300# DIN ND 6,10,16,25,40 Etc.

Type of Flanges

- Inconel Weld Neck Flanges – WNRF
- Inconel Socket Weld Flanges - SWRF
- Inconel Slip On Raise Face - SORF
- Inconel Blind Raise Face – BLRF
- Inconel Lap Joint
- Inconel Screwed (Threaded)
- Inconel Long Weld Neck
- Inconel Reducing
- Inconel Spectacle Blind
- Inconel Ring Joint
- Inconel Large Dia Ring

Grade	UNS	W.Nr.	Trade Name
Inconel 600	N06600	2.4816	Inconel 600®, Nickelvacc® 600, Ferrochronin® 600
Inconel 601	N06601	2.4851	Inconel 601®, Pyromet® 601, Nicrofer® 601
Inconel 617®	N06617	2.4663	Inconel 617®, Nicrofer® 617
Inconel 625	N06625	2.4856	Inconel 625®, Chornin® 625, Altemp® 625, Nickelvacc® 625, Haynes® 625 Nicrofer® 6020
Inconel	N07718	2.4668	Inconel 718®, Nicrofer® 5219, Alvac® 718, Haynes® 718, Altemp® 718
Inconel X 750	N07750	2.4669	Inconel X750®, Haynes X750®, Pyromet® X750, Nickelvacc®X750, Nicorros® 7016
Incoloy 800	N08800	1.4876	Incoloy 800®, Ferrochronin® 800, Nickelvacc® 800, Nicrofer® 3220
Incoloy 800H	N08810	1.4876	Incoloy 800H®, Ferrochronin® 800, Nickelvacc® 800, Nicrofer® 3220
Incoloy 800HT	N08811	1.4876	Incoloy 800HT®, Ferrochronin® 800, Nickelvacc® 800, Nicrofer® 3220
Incoloy 825	N08825	2.4858	Incoloy 825®, Nickelvacc® 825, Nicrofer 4241®

Address	:	Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004
E-mail	:	info@rexinostainless.com , export@rexinostainless.com
Visit Us	:	www.rexinostainless.com
Contact Person	:	Mr. Bhavesh Chandan
Mobile	:	+91- 9920773453



Technical Specification

150 LB. FLANGES

Normal pipe size	Outside dia. of flange	Minimum thickness of flange	Overall Length			Bolt Circle	No. and Size of Holes		O.D. of raised face
			Welding neck	Slip-on & socket welding	Lap Joint		No.	dia.	
	O	Q	Y			Diam.			R
1/2	89	11.2	47.6	15.7	15.7	60.5	4	15.7	35.1
3/4	99	12.7	57.2	15.7	15.7	69.9	4	15.7	42.9
1	108	14.3	55.6	17.5	17.5	79.2	4	15.7	50.8
1.1/4	117	15.7	57.2	20.6	20.6	89.9	4	15.7	63.5
1.1/2	127	17.5	61.9	22.4	22.2	98.6	4	15.7	73.2
2	152	19.1	63.5	25.4	25.4	120.7	4	19.1	91.9
2.1/2	178	22.4	69.9	28.4	28.4	139.7	4	19.1	104.6
3	191	23.9	69.9	30.2	30.2	152.4	4	19.1	127
3.1/2	216	23.9	71.4	31.8	31.8	177.8	8	19.1	139.7
4	229	23.9	76.2	33.3	33.3	190.5	8	19.1	157.2
5	254	23.9	88.9	36.6	36.6	215.9	8	22.4	185.7
6	279	25.4	88.9	39.6	39.6	241.3	8	22.4	215.9
8	343	28.4	101.6	44.5	44.5	298.5	8	22.4	269.7
10	406	30.2	101.6	49.3	49.3	362.0	12	25.4	323.9
12	483	31.8	114.3	55.6	55.6	431.8	12	25.4	381
14	533	35.1	127.0	57.2	79.2	476.3	12	28.4	412.8
16	597	36.6	127.0	63.5	87.4	539.8	16	28.4	469.9
18	635	39.6	139.7	68.3	93.8	577.9	16	31.8	533.4
20	699	42.9	144.5	73.2	103.1	635.0	20	31.8	584.2
24	813	47.8	152.4	82.6	111.3	749.3	20	35.1	692.2

Address	:	Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004
E-mail	:	info@rexinostainless.com , export@rexinostainless.com
Visit Us	:	www.rexinostainless.com
Contact Person	:	Mr. Bhavesh Chandan
Mobile	:	+91- 9920773453