



Monel Flanges



Monel Flanges manufacture and supply by us that are fabricated using graded raw material in the output procedure with different dimensional specifications. It has different features such as durable, high tensile strength, corrosion and oil & temperature resistance. Suitable in diverse industrial applications which has an accurate drilled hole for perfect installation with affordable costs. These flanges are precision engineered and advanced technology with international standard quality monel alloy.

Our own array of monel flanges usually are suitable for applications within assorted sectors. These kind of flanges have precisely drilled pit intended for ideal installation. We can deliver monel flanges in various dimensional specs at most competitive prices.

We are a leading manufacturer and supplier of monel flanges which might be fabricated employing graded raw material inside the creation course of action. These kind of accuracy manufactured monel flanges usually are resilient, resistance to corrosion as well as oil & temperature and have absolutely higher tensile energy. These kind of monel flanges are utilized having stub end or maybe daft that's butt welded towards the pipe using the flange shed behind the idea. It indicates the stub end or maybe daft makes the face. This lap joint is great for minimal stress programs the way it is simply put together in addition to aimed. These kind of could be provided with out a center and/or in dealt with, coated carbon steel so that you can minimize expense.

Specifications:

Standards: ASTM / ASME SB 564

Grades: Monel 400 (UNS No. N04400), Monel 500 (UNS No. N05500)

Size: 1/8" NB TO 48"NB

Address	:	Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004
E-mail	:	info@rexinostainless.com , export@rexinostainless.com
Visit Us	:	www.rexinostainless.com
Contact Person	:	Mr. Bhavesh Chandan
Mobile	:	+91- 9920773453



Forms of flanges:

- Socket Weld
- Weld Neck
- Slip on
- Long Weld Neck
- Blind
- Reducing
- Lapped
- Spectacle
- Screwed
- Ring Joint

Technical Specification



300 LB. FLANGES

Address	:	Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004
E-mail	:	info@rexinostainless.com , export@rexinostainless.com
Visit Us	:	www.rexinostainless.com
Contact Person	:	Mr. Bhavesh Chandan
Mobile	:	+91- 9920773453



Normal pipe size	Outside dia. of flange	Minimum thickness of flange	Overall Length			Bolt Circle	No. and Size of Holes		O.D. of raised face
			Welding neck	Slip-on & socket welding	Lap Joint		No.	dia.	
	O	Q	Y			Diam.			R
1/2	95	14.2	52.3	22.4	22.4	66.5	4	15.7	35.1
3/4	117	15.7	57.2	25.4	25.4	82.6	4	19.1	42.9
1	124	17.5	62	26.9	26.9	88.9	4	19.1	50.8
1-1/4	133	19.1	65	26.9	26.9	98.6	4	19.1	63.5
1-1/2	155	20.6	68	30.2	30.2	114.3	4	22.4	73.2
2	165	22.4	69.9	33.3	33.3	127.0	8	19.1	91.9
2-1/2	191	25.4	76.2	38.1	38.1	149.4	8	22.4	104.6
3	210	28.6	79.2	42.9	42.9	168.1	8	22.4	127
3.1/2	229	30.2	81	44.5	44.5	184.2	8	22.4	139.7
4	254	31.8	85.9	47.6	47.8	200.2	8	22.4	157.2
5	279	35.0	98.6	50.8	50.8	235.0	8	22.4	185.7
6	318	36.6	98.6	52.3	52.3	269.7	12	22.4	215.9
8	381	41.1	111.3	62	62	330.2	12	25.4	269.7
10	445	47.8	117.3	66.5	95.3	387.4	16	28.4	323.9
12	521	50.8	130	73.2	101.6	450.9	16	31.8	381
14	584	53.8	142.7	76.2	111.3	514.4	20	31.8	412.8
16	648	57.2	146.1	82.6	120.7	571.5	20	35.1	469.9
18	711	60.5	158.8	88.9	130.2	628.7	24	35.1	533.4
20	775	63.5	162.1	95.3	139.7	685.8	24	35.1	584.2
24	914	69.9	168.1	106.4	152.4	812.8	24	41.1	692.2

Address	:	Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004
E-mail	:	info@rexinostainless.com , export@rexinostainless.com
Visit Us	:	www.rexinostainless.com
Contact Person	:	Mr. Bhavesh Chandan
Mobile	:	+91- 9920773453