



Stainless Steel Flanges

Stainless Steel Flanges, We are the biggest supplier and exporter of different kinds of **S.S. flanges** whose application in different commercial enterprises and is recognized for their durability and quality. The flanges that we offer to our customers are accessible in diverse evaluations and qualities. They work proficiently with different applications and last more than the conventional flanges. The superior arranged flanges we exchange are utilized on supplies used for nozzles and in piping systems and others.

Size: 1/8" NB TO 48"NB.

Class : 150#, 300#,400 #,600#,900#, 1500# & 2500 #

Stainless Steel Forged Flanges

Stainless Steel Forged Flanges, We exchange steel flanges of diverse evaluations and standard ranges that consent to national & global norms. We can likewise offer flanges according to the client's necessity.

The Grades are as follows

F 304, 304L, 304H, 309S, 309H, 310S, 310H, 316, 316TI, 316H, 316L, 316LN, 317, 317L, 321, 321H, 347, 347H, 904L.



Stainless Steel Slip on Flanges

Stainless Steel Slip on Flanges are slipped over the pipe and afterward file welded. Slip-on flanges are not difficult to use in fabricated applications.

Stainless Steel: ASTM A 182, A 240

Grade : F 304, 304L, 304H, 316, 316



| | | |
|-----------------------|---|---|
| Address | : | Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004 |
| E-mail | : | info@rexinostainless.com , export@rexinostainless.com |
| Visit Us | : | www.rexinostainless.com |
| Contact Person | : | Mr. Bhavesh Chandan |
| Mobile | : | +91- 9920773453 |



REXINO
STAINLESS & ALLOYS

Stainless Steel Blind Flanges

Stainless Steel Blind Flanges are utilized to clear off pipelines, valves and pumps; it can likewise be utilized as an assessment spread. It is once in a while alluded to as a blanking flange.

Stainless Steel: ASTM A 182, A 240

Grade : F304, 304L, 304H, 316, 316L, 316Ti, 310, 310S, 321, 321H, 317, 347, 347H, 904L, Duplex stainless steel UNS S31803, 2205, Super Duplex stainless steel UNS S32750



Stainless Steel Threaded Flanges

Stainless Steel Threaded Flanges are alluded to as either strung or screwed. It is utilized to join other strung segments in low weight, non-discriminating applications. No welding is needed.

Stainless Steel: ASTM A 182, A 240

Grade : F 304, 304L, 304H, 316, 316L, 316Ti, 310, 310S, 321, 321H, 317, 347, 347H, 904L, Duplex stainless steel UNS S31803, 2205, Super Duplex stainless steel UNS S32750



Stainless Steel Socket Weld Flanges

Stainless Steel Socket Weld Flanges are counter exhausted to acknowledge the channel before being filleted welded. The drag of the pipe and flange are both the same along these lines giving great stream attributes.

Stainless Steel: ASTM A 182, A 240

Grade : F 304, 304L, 304H, 316, 316L, 316Ti, 310, 310S, 321, 321H, 317, 347, 347H, 904L, Duplex stainless steel UNS S31803, 2205, Super Duplex stainless steel UNS S32750



| | | |
|-----------------------|---|---|
| Address | : | Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004 |
| E-mail | : | info@rexinostainless.com , export@rexinostainless.com |
| Visit Us | : | www.rexinostainless.com |
| Contact Person | : | Mr. Bhavesh Chandan |
| Mobile | : | +91- 9920773453 |

TECHNICAL SPECIFICATION:

2500 LB. FLANGES



| Normal pipe size | Outside dia. of flange | Minimum thickness of flange | Overall Length | | | Bolt Circle | No. and Size of Holes | | O.D. of raised face |
|------------------|------------------------|-----------------------------|----------------|--------------------------|-----------|-------------|-----------------------|------|---------------------|
| | | | Welding neck | Slip-on & socket welding | Lap Joint | | No. | dia. | |
| | O | Q | Y | | | Diam. | | | R |
| 1/2 | 133 | 30.2 | 73.2 | 39.6 | 39.6 | 88.9 | 4 | 22 | 34.9 |
| 3/4 | 140 | 31.8 | 79.2 | 42.9 | 42.9 | 95.3 | 4 | 22 | 42.9 |
| 1 | 159 | 35.1 | 88.9 | 47.6 | 47.6 | 108.0 | 4 | 25 | 50.8 |
| 1-1/4 | 184 | 38.1 | 95.3 | 52.3 | 52.3 | 130 | 4 | 29 | 63.5 |
| 1-1/2 | 203 | 44.5 | 111.3 | 60.5 | 60.5 | 146.1 | 4 | 32 | 73.0 |
| 2 | 235 | 50.8 | 127.0 | 69.9 | 69.9 | 171.5 | 8 | 29 | 92.1 |
| 2-1/2 | 267 | 57.2 | 142.7 | 79.2 | 79.2 | 196.9 | 8 | 32 | 104.8 |
| 3 | 305 | 66.5 | 168.1 | 91.9 | 92.9 | 228.6 | 8 | 35 | 127.0 |
| 4 | 356 | 76.2 | 190.5 | 108.0 | 108. | 273.1 | 8 | 41 | 157.2 |
| 5 | 419 | 91.9 | 228.6 | 130.2 | 130. | 323.9 | 8 | 48 | 185.7 |
| 6 | 482.3 | 108.0 | 273.1 | 152.4 | 152.4 | 368.3 | 8 | 54 | 215.9 |
| 8 | 552. | 127.0 | 317.5 | 177.8 | 177.8 | 438.2 | 12 | 54 | 269.9 |
| 10 | 673 | 165.1 | 419.1 | 228.6 | 228.6 | 539.8 | 12 | 67 | 323.9 |
| 12 | 762 | 184.2 | 463.6 | 254.0 | 254.0 | 619.3 | 12 | 73 | 381.03 |

| | | |
|-----------------------|---|---|
| Address | : | Rexino Stainless & Alloys, Shop No. 6, Ghojaria Estate no. 2 Kharwa Lane, 6th Kumbharwada Kumbharwada Mumbai- 400004 |
| E-mail | : | info@rexinostainless.com , export@rexinostainless.com |
| Visit Us | : | www.rexinostainless.com |
| Contact Person | : | Mr. Bhavesh Chandan |
| Mobile | : | +91- 9920773453 |